



96 Union elbow, taper seat, ISO/EN UA11

Torque and notes for installation please find in "Technical Product Notes".
374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
* Inside hexagon

EN	Dim.	374 G	Black	Galvanised	a	c	z1	z2	s1	s2
	(inch)	(inch)	Code	Code	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
•	¼	⅝	770 096 102	770 096 202	48	21	11	38	*10	28
•	⅜	¾	770 096 103	770 096 203	52	25	15	42	*12	32
•	½	1	770 096 104	770 096 204	58	28	15	45	25	41
•	¾	1 ¼	770 096 105	770 096 205	62	33	18	47	32	48
•	1	1 ½	770 096 106	770 096 206	72	38	21	55	38	55
•	1 ¼	2	770 096 107	770 096 207	82	45	26	63	48	67
•	1 ½	2 ¼	770 096 108	770 096 208	90	50	31	71	54	74
•	2	2 ¾	770 096 109	770 096 209	100	58	34	76	66	90
-	2 ½	3 ½	770 096 110	770 096 210	130	72	45	103	85	111
-	3	4	770 096 111	770 096 211	134	79	49	104	96	131